



## Universal TAU-II™ Crash Cushion



### Features

- > Approved to NCHRP 350 TL-1, 2 and 3
- > Lowest life cycle cost cushion available
- > Fully re-directive crash cushion
- > Provided in lengths to suit 50kph – 100kph impact speeds
- > Ideally suited as permanent protection of roadway hazards from 1000mm to 2440mm in width
- > Multiple foundation and transition options available
- > Ease of installation
- > Low maintenance, high reusability of system components
- > Delivered assembled
- > No debris build up due to open architecture



### Specifications

- > Designed to stand alone or attach to permanent or portable concrete barrier
- > Steel elements are hot dip galvanised
- > Plastic components are formulated for long outdoor use
- > Hazard widths: 1000mm – 2440mm max
- > Three foundation options are available. The most common being a 28 Mpa non reinforced concrete slab, 200mm thick
- > Transitions to: concrete, W-Beam and Thrie-Beam
- > Design speeds: 50kph - 100kph



More information on Universal TAU-II™ Crash Cushion can be found at [www.acprod.com.au](http://www.acprod.com.au) or call 02 8708 4400

**Manufacturers of Road Safety Barriers | Australian Construction Products Pty Limited**

**New South Wales**  
Sydney 02 8708 4400

**Victoria**  
Melbourne 03 8773 5300

**Queensland**  
Brisbane 07 3442 6200

**Western Australia**  
Perth 02 8708 4400

[www.acprod.com.au](http://www.acprod.com.au)