



\* SPACING SHOWN APPLICABLE TO ALL STATES EXCEPT FOR VICTORIA, WHICH IS 2500 MM.  
 \*\* RAIL HEIGHT VARIES ACROSS STATES, REFER TO STATE ROAD AUTHORITY W BEAM ARRANGEMENT DETAIL.  
 TRANSITION RAIL HEIGHT FROM 790 (MAX-T) TO PUBLIC DOMAIN RAIL HEIGHT OVER TWO RAIL LENGTHS.

REV	DESCRIPTION	APPD	DATE
C	MOTORCYCLIST PROT. COVER AMENDED	W.R.	23.08.21
B	MOTORCYCLIST PROT. COVER ADDED	W.R.	02.04.20
A	ORIGINAL ISSUE	W.R.	21.01.19



**ACP**  
 AUSTRALIAN CONSTRUCTION PRODUCTS  
 Australian Construction Products Pty Ltd  
 339 Horsley Road Milperra NSW 2214  
 P.O. Box 565 Panania NSW 2213  
 Tel: +61 2 9772 4172 Fax: +61 2 9792 6272

TOLERANCES
Whole Numbers $\pm 2$
One Decimal Place $\pm 0.05$
Bend Angle : $\pm 2$
Straightness : $1.5 \text{ per } 1500$
Scale: N.T.S.

CLIENT
MATERIAL
FINISH

ITEM	MAX-TENSION TL-3 TANGENT SYSTEM TRANSITION TO PUBLIC DOMAIN G4 W BEAM		
DRAWING NUMBER			
DRAWN	CHECKED	APPROVED	
W.R.			